

Global Pioneer in NDT Consumables & Equipment



MATERIAL SAFETY DATA SHEET ZChek – DL

Prepared according to the Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Prepared: Dec-22 Supersedes: 03

Section 1: Product and Company Identification

1.1Product Name: ZChek- DL

1.2Product Use: Developer for Dye Penetrant Inspection Process.

1.3Manufacturer Information: ZChemSpecialities Private Limited.

Sy. No.11/2/6, Puradapalya Village TavarekereHobli, Bangalore, Karnataka-562130, India

Website: www.zchem.in

Emergency Telephone Number: +91-9959963334

Section 2: Hazards Identification

2.1 Hazard Classification

This product is hazardous under the criteria of the hazardous product regulation as implemented under WHMIS 2015.

Flammable Liquids: Category 2 Eye irritation: Category 2A

Specific Target Organ Toxicity: Single exposure- Category 3

2.2 Label Elements

 \cdot Labelling according to Regulation (EC) No 1272/2008 The product is classified and labeled according to the CLP regulation.





Hazard pictograms

Signal word: Danger

2.3 Hazard Statements

- H225Highly Flammable liquid and vapors.
- H319Cause serious eye irritation.
- H336May cause drowsiness or dizziness.

2.4 Precautionary statement

- P210Keep away from heat, sparks, open flames, hot surfaces. No smoking.
- P241Use explosion- proof electrical, ventilating, lighting, equipment.
- P305+P351+P338 If in eyes- rinse cautiously with water for several minutes.
- P303+P361+P353Wash skin thoroughly after handling.
- P405Keep container tightly closed.





**** +91 73491 77755, +91 73492 77755







Global Pioneer in NDT Consumables & Equipment




2.5 Classification system

NFPA ratings (scale0-4)



HMIS -ratings (scale0-4)



Health=1 Fire=3 Reactivity=0

2.6 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable vPvB: Not applicable

Section 3 - Information on Ingredients

| Ingredient | CAS# | Wt/wt% |
|--------------|------------|--------|
| Propan- 2-ol | 67-63-0 | 40-70% |
| Propan-2-one | 67-64-1 | 10-30% |
| Talc | 14807-96-6 | 1-3% |

Section 4 - First Aid Measures


Eyes:Rinse carefully using plenty of water.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. DO NOT use ointments. Seek medical attention if irritation persists.

Inhalation:Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.

Ingestion:DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. DO NOT leave victim unattended. Seek medical attention immediately.













Global Pioneer in NDT Consumables & Equipment



Section 5: Fire Fighting Measures

5.1 Extinguishing media

Suitable extinguisher agents:

- CO2, sand, extinguishing powder. Do not use water.
- Water haze
- Foam
- **ABC** Powder

For safety reasons unsuitable extinguishing agents: Water with full jet.

5.2 Advice for fire fighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Section 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

6.2 Environmental precautions: Do not allow to enter sewers, surfaces or ground water.

6.3 Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents.
- Collect liquid in an appropriate containers or absorb with an inert materials such as vermiculite, dry sand or earth; DO NOT use combustible materials.
- Place in a chemical waste container.

Section 7: Handling and Storage

7.1Prevention for safe handling:

- DO NOT allow material to come in contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.
- Protect against electrostatic charges.
- Use explosion-proof apparatus/fittings and spark-proof tools.
- Containers may be hazardous when empty since residue liquid and vapors may be present.

7.2 Conditions for safe Storage:

- No smoking.
- Store in cool, dry conditions in well-sealed receptacles

Section 8: Exposure Controls and Personal Protection

8.1 Control Parameters



Sy.No. 11/2/6, Puradapalya Village Tavarekere Hobli, Bangalore, Karnataka - 562130, India









Global Pioneer in NDT Consumables & Equipment



| Proper 2 of (47.42.0) | | | | |
|------------------------|----------------------------------|-------------------------------|--|--|
| Propan- 2-ol (67-63-0) | T | | | |
| ACGIH | ACGIH TWA (ppm) | 200 ppm | | |
| ACGIH | ACGIH STEL (ppm) | 400 ppm | | |
| OSHA | OSHA PEL (TWA) mg/m ³ | 980 mg/m ³ | | |
| OSHA | OSHA PEL (TWA) (ppm) | 400 ppm | | |
| USA-IDLH | US IDLH (ppm) | 2000 ppm(10% LEL) | | |
| USA –NIOSH | NIOSH REL (TWA) (mg/m3) | 980 mg/m ³ | | |
| USA –NIOSH | NIOSH REL (TWA) (ppm) | 400 ppm | | |
| USA- NIOSH | NIOSH REL (STEL) (mg/m3) | 1225 mg/m3 | | |
| USA -NIOSH | NIOSH REL (STEL) (ppm) | 500 ppm | | |
| Propan-2-one (67-64-1) | | | | |
| ACGIH | ACGIH TWA (mg/m³) | 1188 mg/m ³ /8h | | |
| ACGIH | ACGIH TWA (ppm) | 500 ppm/8h | | |
| ACGIH | ACGIH STEL (mg/m ³) | 1782 mg/m ³ /15min | | |
| ACGIH | ACHIH STEL (ppm) | 750 ppm/15min | | |
| OSHA | OSHA PEL (TWA) mg/m ³ | 2400 mg/m ³ | | |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm | | |
| USA-IDLH | US IDLH (ppm) | 2500 ppm(10% LEL) | | |
| USA -NIOSH | NIOSH REL (TWA) (mg/m3) | 590 mg/m ³ /10h | | |
| USA –NIOSH | NIOSH REL (TWA) (ppm) | 250 ppm/10h | | |

8.2. Exposure Controls

Engineering Controls: Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines mentioned above.

Personal protection: Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable. Respirator with filter if sprayed in enclosed unventilated space.







General Hygiene Considerations: Wash thoroughly after handling. Have eye-wash facilities immediately available.

Section 9: Physical and Chemical Properties

Appearance:

Form: White liquid Color: White Odor: Characteristic


Odor threshold: Not determined. pH value: Not applicable Melting point: Not determined. Boiling point: Not determined.

Flammability - Not applicable



Sy.No. 11/2/6, Puradapalya Village Tavarekere Hobli, Bangalore, Karnataka - 562130, India









Global Pioneer in NDT Consumables & Equipment



Flash point: - 16deg.C

Ignition temperature: No data available Decomposition temperature: Not determined.

Auto-ignition temperature- Product is not self-igniting.

Vapour pressure at 20 deg.C: Not determined

Evaporation rate: Not determined

Solubility /miscibility with water: Not miscible or difficult to mix

Partition Coefficient: Not determined

Viscosity:

Dynamic- Not determined Viscosity- Not determined

VOC Content: 86%

Vapor density: No data available Evaporation rate: No data available

Section 10: Stability and Reactivity

Stability:Stable.

Conditions to Avoid:Keep away from heat and ignition sources.

Incompatibility:None

Hazardous Decomposition: When burning, soot, oxides of carbon and nitrogen.

Reactivity: None

Section 11: Toxicological Information

| Propan- 2-ol (67-63-0) | | |
|------------------------|--------------------|--|
| LD 50 oral rat | 5840 mg/kg | |
| LD 50 dermal rabbit | >12800 mg/kg | |
| LC 50 inhalation rat | >10000 ppm/6h | |
| Propan-2-one (67-64-1) | | |
| LD 50 oral rat | 5800 mg/kg | |
| LC 50 inhalation rat | 76 mg/l/4h(female) | |
| LC 50 inhalation rat | 132 mg/l/3h (Male) | |

Primary irritant effect

- Skin: No irritant effect.
- Eye: Irritating effect
- Sensitization: No sensitizing effects known





Global Pioneer in NDT Consumables & Equipment



Carcinogenic categories

IARC(International Agency for Research of Cancer)-67-63-0 Propan-2-ol **- 3**

NTP (National Toxicology Program) - None of the ingredients is listed

OSHA-Ca (Occupational Safety and Health Administration)-None of the ingredients is listed

Section 12: Ecological Information

12.1.Ecology: General: May cause long term adverse effect in the aquatic environment.

12.2. Persistence and degradability: No further relevant information available.

12.3. Bio accumulative potential: No further relevant information available

12.4. Mobility in soil: No further information available.

Water hazard class1(self- assessment): slightly hazardous for water.

Section 13: Disposal Considerations

13.1. Waste treatments methods

Recommendation:

- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Waste/unused products
- Collect all waste in suitable and labeled containers and dispose according to local legislation.

13.2. Un-cleaned packaging's:

Recommendation:

Waste/used products

Waste products and empty packages dispose of in accordance with local regulations.

Empty containers may contain flammable residues.

Section 14: Transport Information

| 14.1 UN -Number DOT, ADR,IMDG,IATA | UN 1993 |
|--|---|
| 14.2 UN proper shipping name DOT - ADR- IMDG- IATA- | Flammable liquid n.o.s. (Isopropanol) Flammable liquid n.o.s. (Isopropanol) Flammable liquid n.o.s. (Isopropanol) Flammable liquid n.o.s. (Isopropanol) |






Global Pioneer in NDT Consumables & Equipment

| 14.3 Transport Hazard class(es) | | |
|---|--|--|
| DOT | Class 3 Flammable liquid | |
| | Label-3 | |
| ADR, IMDG,IATA | Class 3 Flammable liquid | |
| | Label-3 | |
| 14.4 Packing group | | |
| DOT,ADR,IMDG,IATA | II | |
| 14.5 Environmental hazards | | |
| Marine pollutant | No | |
| 14.6 Special precautions for user | Warning: Flammable liquids | |
| Danger code(Kemler): | 33 | |
| EMS Number: | F-E,-S-D | |
| 14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code | Not applicable | |
| Transport/ Additional information: DOT Quantity limitations On passenger aircraft/ railway :- 5 ltr On cargo aircraft only:- 60 ltr | | |
| Maximum net quantit | Q) Code: E2 Maximum net quantity per inner packaging- 30 ml Maximum net quantity per outer packaging -500 ml | |
| IMDG Limited quantites (LQ) 1 L | s (LQ) 1 L | |













Global Pioneer in NDT Consumables & Equipment



IATA

Remarks: Quantity Limitation- Passenger Air craft- 5ltr

Quantity Limitation- Cargo Aircraft 60 ltr Quantity limitation – Limited quantities- 1ltr

Packaging Instruction: Passenger Aircraft- PI 353 Cargo aircraft-PI 364 Limited quantities –PI Y341

UN "Model Regulation" UN 1993 Flammable liquid n.o.s (Isopropyl alcohol),,3,II

Section 15: Regulatory Information

15.1 Safety, Health and Environmental Regulations/ Legislation specific for the substance or mixture.

- SARA:- Section 355 (extremely hazardous substances): None of the ingredient is listed
- **Section 313** (Specific toxic chemical listings); 67-63-0 propan-2-ol
- TSCA (Toxic Substance Control Act):-All components listed
- Proposition 65
- **Chemicals Known to cause cancer:** None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.
- Chemicals known to cause developmental toxicity: None of the ingredients is listed.
- Carcinogenicity Categories
- **EPA (Environmental Protecting Agency)** –None of the ingredients listed.
- TLV(Threshold Limit Value established by ACGIH)-67-63-0 propan-2-ol
- NIOSH (National Institute For Occupational Safety And Health)-None of the ingredients is listed.

15.2 Chemical safety assessment:- A Chemical Safety Assessment has not been carried out. Note: This MSDS has been prepared to meet WHMIS (Canada) requirements with the expectation of using 16 headings.

Section 16: Other Information

Disclaimer To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Doc No.: ZChem/Msds/DL/C001/Dec-22(Version-4)



