

Inspection Certificate (In accordance with EN 10204 Type-3.1)

Product: ZChek -9E Black

Non-Fluorescent MPI Suspension

Batch No.: 240906

Mfg. Date: 09/24

We certify that the above product, when tested at the time of manufacturing meets the following requirements

- *ASME Boiler and Pressure Vessel Code 2010, 2013, 2017, 2019, 2021, 2023 Edition Section V, Nondestructive Examination including, Article 7, including 2005, 2006, 2008, 2009b and 2011a Addenda, paragraph T-731, paragraph T-765 and Article -25 as applicable.*
- *ASTM E 709-21 paragraph 2.2*
- *AMS 3041F, AMS 3043E, AMS 2641D*

Parameter	Test Method	Quality requirement	Batch Result
Contamination	AMS 3041F-3.3.1	No foreign material, scum, or agglomeration	Confirms
Concentration	AMS 3041F-3.3.2	1.0-2.4ml per 100ml	1.7ml per 100ml
Sensitivity	AMS 3041F-3.3.3	6 Hole indication shown	6 Hole indication
Color	AMS 3041F-3.3.4	Black	Black
Particle size	AMS 3041F-3.5	< 2 % residue on 45μ mesh	1.6 % residue on 45μ mesh
Mechanical durability	AMS 3041F -3.6	Retain initial sensitivity and color	Confirms
Spray ability and leakage	AMS 3043E-3.4	No perceptible leakage. Uniform spray pattern and No chunking and clogging of the nozzle	Confirms
Viscosity	AMS 2641D-3.2.2	< 3cSt @ 38 deg. C	2.51cSt @ 38deg.C
Flash point	AMS 2641D-3.2.1.1 Type-1	> 93deg.C	104deg.C
Odor	AMS2641D- 3.2.6	No offensive, No objectionable odor	Confirms
Color	AMS 2641D-3.2.7	Not darker than No.1 ASTM color	Confirms



- *ASTM E3024/E3024M-22A*
- *ASTM E1444/E1444-21 Paragraphs 5.8.2, 5.8.3 & 5.8.5*
- *ASTM E 709-21, Paragraphs 8.1, 8.2, 8.4, 8.4.3, 8.4.4, 8.4.4.1, 8.4.5, & 8.4.6*
- *EN ISO 9934-2-2015*

Parameter	EN ISO 9934-2	Quality requirement	Batch Result
Performance	7.1	Indication on Reference block-1 Reference block-2	Pass Length-6cm
Color	7.2	Black liquid	Color identical
Particle size	7.3	d> 1.5µm -d< 40 µm	dl(10%)=0.635µm da(50%)=1.76µm du(90%)=4.26 µm
Flash point	7.7	Report as found	104deg.C
Viscosity	7.9	Less than 5.0mPa @ 20deg.c	4.0mPa @ 20deg.C
Mechanical stability test Short term test	7.10	No degradation in sensitivity	Pass
Foaming	7.11	No significant foaming	Pass
Storage stability	7.13		3 years
Content of sulphur	7.15	< 200ppm	33ppm
Content of halogens (chlorine & fluorine)	7.15	< 200ppm	65ppm

Notes

1. Bulk material has a minimum shelf life of 5 years and Aerosol has minimum shelf life of 3 years.
2. EN ISO 9934-2 (7.15) specification require test results stated in ppm, but some require in percentage. To convert ppm to percentage, divide the ppm value by 10,000.

Signature

Manager Operations

