

# Product Data Sheet ZGhek-FP12



### **Post Emulsifiable Fluorescent Penetrant**

### Type 1 Method B, C & D Sensitivity Level 3

### **DESCRIPTION**

ZChek-FP12 is a High Sensitivity Post Emulsifiable Fluorescent Penetrant for detecting fine discontinuities open to surface. It exhibits outstanding fluorescent brightness. FP12 is a versatile high sensitivity penetrant for use on a variety of materials in critical applications for Aviation/ Aerospace and Engineering Industries.

### **CONFORMANCE / APPROVALS**

- AMS 2644
- ASME B & PV Code. Sec V
- ASTM E165
- ASTM E1417
- ISO 3452-2

### **FEATURES / BENEFITS**

- Sharp indications and zero background for visibility.
- Super Bright Excellent Indications
- Resists over-washing High Sensitivity
- High flash point Safe on all areas
- Non-halogenated Safe on all metals.
- Low Odor User friendly.



### **APPLICATIONS**

ZChek-FP12 is used in the inspection and detection of discontinuities in castings, forgings, extrusions and other metal surfaces in Aviation / Aerospace, Oil & Gas and Engineering Industries.

### TYPICAL PROPERTIES

Colour	Bright Green-Yellow
Viscosity @ 40°C	12 cSt
Density @ 29.5°C	0.87 g /cc
Flash point	> 93 deg. C
Sulfur	< 1000 ppm
Chloride	< 1000 ppm
Fluoride	< 50 ppm



### **Product Data Sheet**

## Zehek-FP12



### **DIRECTIONS FOR USE**

- Apply FP12 on a clean, dry surface by spraying, flowing, brushing or dipping method.
- Dwell time suggested is 10 minutes. If the part is especially critical the dwell time may be extended to 30 minutes or longer. Allow the penetrant to drain from the part surface.
- For Method C Solvent Removable method use ZChek Cleaner
- For Method D Post Emulsifiable Hydrophilic use ZChek-EF9
- For Method B Post Emulsifiable Lipophilic use ZChek-EF81
- Follow ASTM E1417 for the further process.

### **PACK SIZES**

- 20-liter Can Part # 120804
- 5-gallon Pail- Part #120803
- 205-liter Drum Part #120806
- 55-gallon Barrel Part #120805
- Aerosol cans of 520 ml 12 cans in one carton box Part #120801

### **HEALTH & SAFETY**

Information on Health & Safety is made available through Material Safety data sheet & the same can be reviewed through the company's website <a href="www.zchem.in">www.zchem.in</a>.

# Solvent Removable i Post Emulvilled Putonscent Penetrani Type 1 Method B.C &D, Sensitivity Level - 3 For Liquid Penetrant Inspection Features - Benefits • Sharp Indications and zero background for enhanced visibility • High sensitivity results in detection of fine detects • High flash point - safe in open areas • Non hadiogenated - safe on all metals Approvals I Confirms to • ASTME ELES • ASTME 165 • ASTME 117 • EN ISO 3482-2 For Industrial use by Qualified Paraconal Only

### **STORAGE & SHELF LIFE**

Aerosol cans have a shelf life of 3 years and the bulk packing of 5 years if unopened & stored as per ZChem recommendations.

### Registered office and factory:

### **ZChem Specialities Pvt. Ltd.**

Sy,No.11/2/6, Puradapalya Village, Tavarekere Hobli, Bangalore – 562130, India Phone +917349177755 & +917349277755 Email - <u>info@zchem.in</u>, Website - <u>www.zchem.in</u>

### **Branch Office:**

### **ZChem Specialities BFC**

BLB-S5-384, Ajman Media City, Ajman, UAE Email - info@zchem.in, Website - www.zchem.in

Disclaimer: We have taken best care to ensure that the information provided in this data sheet is accurate. Our product is guaranteed to conform to the specifications provided. We make no other warranty; hence the liability is limited to replacement of product only.